

# INTER ROW BLADE KIT H



45 - 55 - 65 cm LH or RH inter-row blade, with quick tractor couplings and bulldozer-like tilling spur without emergency blade return

(if blade return is necessary: code 1184 / 1185 for the single version or code 1189 for the double version)

**Model**



**Kit lama interceppo H dx**

1352

0

**Kit lama interceppo H sx**

1353

0

## Optional

- CODE 1184 - Manual mechanical emergency blade return

- CODE 1185 - Manual electrohydraulic emergency blade return with kit electrovalve

- CODE 1363 - Contemporary manual electrohydraulic emergency blades return with kit valves
- CODE 1189 - Electrohydraulic emergency return of each blade separately and RH and LH simultaneously with the electrical control unit with kit valves
- CODE 1223 - Professional gears divisor of flow (it exactly divides to 50% the flow of oil in entrance) to contemporarily feed the two inter row with only one oil flow coming from the hydraulic installation of the tractor avoiding to overheat the oil of the same installation. It replaces the independent hydraulic system - for H, ECO and TOP models necessary at least 35 liters oil in entrance(max 75 liters) / pressure min bar 120 / temperature oil max 90° Cs. (essential a good system of cooling of the oil) - for the FULL models necessary at least 50 liters oil in entrance (max 75 liters) / pressure min bar 200 / temperature oil max 90° Cs. (essential a good system of oil cooling)
- CODE 0694 - Bulldozer-like tilling spur
- CODE 1160 - RH non-stop feeler pin holder
- CODE 1085 - RH oscillating feeler pin holder adjustable in height
- CODE 1187 - RH 45 cm inter-row plant lifting ploughshare
- CODE 1268 - RH 55 cm inter-row plant lifting ploughshare
- CODE 1266 - Universal no traction adjustable rounded tiller disc
- CODE 1264 - Universal no traction adjustable ridger bit disc

[Print this page](#)