








SUBSOILER SPIDER 5



5-tooth subsoiler with frontal breakaway bolt safety device (indestructible and very effective)

Toothed roller with double mechanical adjustment

Lateral fin with height adjustment

Model							
Spider 5	0807	50 - 80	62	5	150	40	380
Spider 5 L	1255	50 - 80	62	5	170	40	400

Optional

- CODE 1075 - RH and LH 300x100 mm depth adjustment reinforced wheels with bearings with rods to the frame

- CODE 0711 - Type H kit including tank, oil, filter, pump and multiplier

- CODE 0713 - Type H single heat exchanger kit with thermostat

- CODE 0979 - Predisposition for the application of RH inter-row blade (only when ordering)

- CODE 0980 - RH 55 cm inter-row blade kit with quick tractor couplings with mechanical manual emergency return of the H-type blade, complete with chiselling bulldozer-spur (the last tooth on the right must be removed in order to install the inter-row blade (the application of item 0979 is also required)

- CODE 0981 - Stainless steel 18/10, 380-litre curved-tank 2-row fertiliser spreader for pellet and granular fertilisers, hydraulic stirrer with 2 quick tractor couplings, hydraulic closing with quick tractor coupling complete with support for frame application (not applicable on aerator Maxi ext. CODE 1350)

- CODE 1007 - Cm 135, stainless steel 18/10, 200 liters, over-edge for fertiliser spreader art. 0891 (applicable only when ordering)

[Print this page](#)