




CLOSED ROLLER



Perfect for re-compacting surfaces, to avoid evaporation of land humidity during hot, dry periods (standard with mechanical adjustment)

Model	 CODE		 Kg.
per Basic 3	0928	cm 55	0
per Basic 4	0929	cm 70	0
per Basic 5	0930	cm 100	0
per Basic 6+1, 7, 10, 12	0931	cm 132,5	0
per Basic 8+1, 9	0932	cm 190/180 largo corto	0
per prolunga Basic 10 (San Salvo 10)	0933	cm 87	0
per prolunga Basic 12 (San Salvo 12)	0934	cm 100	0

per Vittoria 3	0884	cm 70	0
per Vittoria 4	0885	cm 90 disassato	0
per Vittoria 5	0886	cm 120 disassato	0
per Vittoria 6, 7	0887	cm 132,5	0
per Vittoria 8	0888	cm 170	0
per Vittoria 9	0889	cm 180 largo lungo	0
per Futura 3	0900	cm 86	0
per Futura 5S	0901	cm 132,5	0
per Futura 5	0902	cm 153 corto stretto	0
per Futura 7	0903	cm 153	0
per Futura 9	0904	cm 190	0
per San Salvo 10, 12	0911	cm 147,5 disassato	0

Optional

- CODE 1166 - Pair of toothed stability crests on closed roller (optional applicabile only when ordering)

Print this page