



**Total load:**  
39 000 kg

**Dead weight:**  
11 700 kg

**Basic length:**  
13 600 mm



**Maximum length in extended state:** 16 600 mm

- semi-trailer 2 metres extension (4x500 mm) in the central part, extensible hydraulic ramp in the rear part
- front loading ramps - 3 parts with hydraulic lift and extension
- central part lifted hydraulically (due to continuous drive of vehicles with low driving height)

**SAF:**  
SAF 3x9 t, double fitting R 17,5"

- 1st axle** - Lift axle
- 2nd axle** - Fix axle
- 3rd axle** - Fix axle - steering

**Spring:**  
Air spring - semi-trailer lifting and lowering

**Tyres:**  
235/75 R 17,5" with steel discs

**Brake system:**  
EBS+ 2S/2M HALDEX

**The height of the fifth wheel:**  
950 mm, 1 100 mm, 1 250 mm

**Winch:**  
▪ traction force 6 t

**Accessories for extra charge:**

- **POWER PACK** - it is an electro-hydraulic aggregate that enables to manipulate hydraulic components of semi-trailer without being connected to the hydraulics of the towing vehicle
- **SMARTBOARD** - infocenter
- (counter of driven kilometers, electronic load measuring)
- rear loading ramps (height adjustable by means of hydraulics)